

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

SECTION 1. IDENTIFICATION

Product name : 2000® ARCTIC GRADE

SDS-Identcode : 310G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2777 N. Stemmons Frwy Ste 1800
Dallas TX 75207,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887
(24-hours/7 days)
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Eye irritation : Category 2A

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water
for several minutes. Remove contact lenses, if present and easy
to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ atten-
tion.

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 20 - < 30
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Graphite	7782-42-5	>= 20 - < 30
Talc	14807-96-6	>= 5 - < 10
Copper metal powder	7440-50-8	>= 1 - < 5
Calcium oxide	1305-78-8	>= 1 - < 5
Dolomite	16389-88-1	>= 1 - < 5
Quartz	14808-60-7	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

- Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Fluorine compounds
Metal oxides
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
-

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
 Date of first issue: 05/12/2015

Materials to avoid : Store in accordance with the particular national regulations.
 : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
		Talc	14807-96-6	TWA (Dust)
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Copper metal powder	7440-50-8	TWA (Dust and mist)	1 mg/m ³ (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m ³ (Copper)	ACGIH
		TWA (Dust)	1 mg/m ³ (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m ³ (Copper)	NIOSH REL
		TWA (dusts and mists)	1 mg/m ³ (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m ³ (Copper)	OSHA Z-1
Calcium oxide	1305-78-8	TWA	2 mg/m ³	ACGIH
		TWA	2 mg/m ³	NIOSH REL

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
 Date of first issue: 05/12/2015

		TWA	5 mg/m ³	OSHA Z-1
Dolomite	16389-88-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

Engineering measures : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

time is not determined for the product. Change gloves often!
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid
Color : black, copper
Odor : Petroleum
Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available
Flash point : ≥ 325.0 °F / ≥ 162.8 °C
Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.3

Solubility(ies)
Water solubility : negligible

Partition coefficient: n- : Not applicable

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

octanol/water
Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.
Conditions to avoid : None known.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated light naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Distillates (petroleum), hydrotreated heavy naphthenic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Graphite:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Talc:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Copper metal powder:

- Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Calcium oxide:

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Dolomite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated light naphthenic:

Species : Rabbit
Result : No skin irritation

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Graphite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Talc:

Species : Rabbit
Result : No skin irritation

Copper metal powder:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Calcium oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Dolomite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Species : Rabbit
Result : No eye irritation

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Talc:

Species : Rabbit
Result : No eye irritation

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Copper metal powder:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Calcium oxide:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Dolomite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Graphite:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Talc:

Routes of exposure : Skin contact
Species : Humans
Result : negative

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Copper metal powder:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Calcium oxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Dolomite:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Copper metal powder:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: Directive 67/548/EEC, Annex V, B.12.
Result: negative
Remarks: Based on data from similar materials

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Result : negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

Talc:

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

Calcium oxide:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : negative
Remarks : Based on data from similar materials

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive
Remarks : IARC: (International Agency for Research on Cancer)
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

ment

tion)

IARC

Group 1: Carcinogenic to humans
Quartz
(Silica dust, crystalline)

14808-60-7

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogen
Quartz
(Silica, Crystalline (Respirable Size))

14808-60-7

Reproductive toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Copper metal powder:

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Result: negative

Calcium oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Dolomite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:

Calcium oxide:

Assessment : May cause respiratory irritation.

2000® ARCTIC GRADE

Version Revision Date: SDS Number: Date of last issue: 10/11/2018
9.2 04/11/2019 115243-00016 Date of first issue: 05/12/2015

STOT-repeated exposure

Not classified based on available information.

Components:**Quartz:**

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated light naphthenic:**

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Remarks : Based on data from similar materials

Copper metal powder:

Species : Rat
NOAEL : >= 2 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days

Calcium oxide:

Species : Rat
NOAEL : >= 0.399 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 90 Days
Method : OECD Test Guideline 413

Dolomite:

Species : Mouse
NOAEL : 1,300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Remarks : Based on data from similar materials

2000® ARCTIC GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2018
9.2	04/11/2019	115243-00016	Date of first issue: 05/12/2015

Quartz:

Species	:	Humans
LOAEL	:	0.053 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Remarks	:	These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 1,064,120 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
------------------	---	--

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 15,470 mg/l Exposure time: 96 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
---	---	---

	:	EC50 (Daphnia magna (Water flea)): 30,940 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
--	---	---

Toxicity to algae/aquatic plants	:	EC50 (Selenastrum capricornutum (green algae)): 11,267 mg/l Exposure time: 96 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
----------------------------------	---	--

	:	NOEC (Selenastrum capricornutum (green algae)): 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
--	---	---

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction
------------------	---	---

Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction
---	---	--

2000® ARCTIC GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2018
9.2	04/11/2019	115243-00016	Date of first issue: 05/12/2015

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d

Toxicity to microorganisms : NOEC (Photobacterium phosphoreum): > 2.17 mg/l
 Exposure time: 4 d

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

2000® ARCTIC GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2018
9.2	04/11/2019	115243-00016	Date of first issue: 05/12/2015

Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
 Exposure time: 24 h

Copper metal powder:

Toxicity to fish : LC50: > 10 - 100 µg/l
 Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 10 µg/l

Calcium oxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Crangon crangon (shrimp)): > 1 mg/l
 Exposure time: 14 d
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209
 Remarks: Based on data from similar materials

Dolomite:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l

2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Quartz:**Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability**Product:**

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder, Antimony, dialkyl dithiocarbamate)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Copper metal powder, Antimony, dialkyl dithiocarbamate)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder, Antimony, dialkyl dithiocarbamate)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Copper metal powder, Antimony, dialkyl dithiocarbamate)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(Copper metal powder, Antimony, dialkyl dithiocarbamate)
Remarks : Above applies only to containers over 119 gallons or 450 liters.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Copper metal powder	7440-50-8	5000	132187

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Copper metal powder 7440-50-8 >= 1 - < 5 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Graphite	7782-42-5
Polytetrafluoroethylene	9002-84-0
Talc	14807-96-6
Copper metal powder	7440-50-8
Calcium(2+) 12-hydroxyoctadecanoate	3159-62-4
Calcium oxide	1305-78-8
Quartz	14808-60-7
Antimony, dialkyl dithiocarbamate	15890-25-2

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
Date of first issue: 05/12/2015

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Graphite	7782-42-5
Talc	14807-96-6
Copper metal powder	7440-50-8
Calcium oxide	1305-78-8

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Graphite	7782-42-5
Talc	14807-96-6
Copper metal powder	7440-50-8
Calcium oxide	1305-78-8
Quartz	14808-60-7

California Regulated Carcinogens

Quartz	14808-60-7
--------	------------

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.


2000® ARCTIC GRADE

Version 9.2 Revision Date: 04/11/2019 SDS Number: 115243-00016 Date of last issue: 10/11/2018
 Date of first issue: 05/12/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY	1	
PHYSICAL HAZARD	0	

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Oth-

SAFETY DATA SHEET



2000® ARCTIC GRADE

Version	Revision Date:	SDS Number:	Date of last issue: 10/11/2018
9.2	04/11/2019	115243-00016	Date of first issue: 05/12/2015

erwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/11/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8